СМУК

Pouch Formats

Basic Pouch

3 Side

Specialty Pouch

Zipper



4 Side



Twin

Spout



Handle

OUTE OLIE WEDESE WOUSSE

T-110



T-140



Euro Slot

With 40 years of experience in Design, Development & Manufacturing, 7000+ installations across 45 countries, and 8 offices in India, Nichrome has evolved as a premium brand for all your packaging needs.


Nichrome offers European Technology in Horizontal Form Fill Seal Packaging Machines. The advanced and efficient Horizontal Form Fill Seal Machines incorporate expertise and high-tech capability adhering to international standards & regulations, and modern designs in tune with the market requirements.

Nichrome has developed several innovative solutions for cosmetics, health care, chemicals, dried fruits, juices, concentrates, nectars, syrups, pastes, etc.



T-170 FE and SC

Sealing Patterns









 NICHROME INDIA LTD. Safire Park Galleria, 4, Pune-Mumbai Road, Shivajinagar, Pune - 411 005, India

 Tel.: +91 - 20 - 6601 1001
 Fax: +91 - 20 - 6601 1010
 E-mail: marketing@nichrome.com
 www.nichrome.com

 Service Centres & Offices at:
 Delhi | Kolkata | Mumbai | Bangalore | Hyderabad | Chennai | Ahmedabad

 ASEAN | MIDDLE EAST | SAARC | CIS | AFRICA | USA

Packaging Solutions For • Liquid • Grains • Powders • Seeds • Snacks • Pharma • Personal Care



NICHROME European Technology

Versatile Solutions for all Industries

➢ New Generation


Linear Technology

Pouch Aesthetics



An ISO 9001:2008 and ISO 22000:2005 Certified Company

www.nichrome.com



Free flowing Liquids like Milk, Lassi, Buttermilk, Flavoured Water, Health Drinks,

Non Carbonated Beverages, Liquors & Wines, Oil & Juices.

Salient Features

- PLC based machine with touch screen interface
- Facility to offer single or perforated chain of pouches
- Compact & versatile design
- Auto tuning temperature controller

Technical Specifications

Machine	T-110	T-140	T-170 FE	T-170 SC	T-200		
Volume (cc)							
Simplex	1-60	5250	90—1000	90-1000	90–1500		
Duplex	1–20	590	N.A.	N.A.	45–750		
Rated Output (packs/min)							
Simplex	110	100	45	45	80		
Duplex	220	200			160		
Pouch Formats	3 side seal	3 side seal	3 side seal	(Pre-formed)	3 side seal		
	4 side seal	4 side seal	4 side seal	3 side seal	4 side seal		
		Zipper	Stand up	4 side seal	Stand up		
		Contour/Profile	Zipper	Stand up	Zipper		
			Handle	Zipper	Handle		
			Spout		Spout		
			Contour/Profile		Contour/Profile		
Pack Size Range							
Simplex							
Min. pack size (WxL) mm	(30x30)x1	(70x100)x1	(80x130)x1	(80x130)x1	(100x100)x1		
Max. pack size (WxL) mm	(110x130)x1	(140x200)x1	(170x270)x1	(170x270)x1	(200x300)x1		
Duplex							
Min pack size	(30x30)x2	(50x100)x2	N.A.	N.A.	(70x100)x2		
Max pack size	(65x130)x2	(70x200)x2	N.A.	N.A.	(100x300)x2		
Max. Roll Diameter (mm)	450	450	450	N.A.	450		
Max. Roll Width (standard)	260	400	540	N.A.	600		
Max. Roll Width (stand-up)	N.A.	N.A.	630	N.A.	720		
Core Diameter (mm)	70–75	70–75	70–75	N.A.	70–75		
Power Consumption (kW)							
Simplex	1.8	2	5.9	3.7	6		
Duplex	3	3.2	N.A.	N.A.	6.5		
Machine Dimensions	2120x820x1840	2980x940x2110	4720x1100x2500	2960x980x2500	5560x1070x2350		
(LxDxH) mm							
Supply Voltage	415 V-AC, 3 Phase, 50Hz or equivalent						
Packing Material	Heat sealable laminates like PET/PE, Paper/Alu-foil/PE, Alu/PF, PET/Alu-foil/PE or Co ex films						
Air Consumption	7–10 cfm or 12–17 cubic meter/hr @ 6 bar pressure						

4	сс	es	SC	ori	es

- Twin Pouch Cutter
- Dashed V-shaped Tear Notch
- Euro Slot / Round Hole
- Perforation Round Edge Pouch
- Special Form Matrix
- Funnel / Bottom Vibrator

Special Note: Filler configuration will depend on volume range and other parameters.

Gravity Filler /

Flow Meters

- Mechanically operated horizontal seal system
- Duplex models available for higher ouputs ٠
 - Easy & quick change over

• No fill – No pouch Counter Fill Funnel Tachometer • UV Film Sterilization

Optional Accessories

- Emboss Coder
- Printers
- Counting and Collating of packs
- Gas Flush
- Dust Exhaust / Dust Collector
- Material Handling System